



LAM2 500 / LAM 2 600 有底座丹麥機

The reversible sheeters mod. LAM 500/600 were specifically designed with the particular consideration for use within small bread-pastry bakeries, hotels and restaurants. For industrial needs it is available the LAM 6500 that allows to work a bigger amount of dough. In all the LAM sheeters the conveyor tables can be raised up into a resting position, thereby occupying less space within the working area. This position also facilitates effective cleaning of the unit. The absence of uncovered and unprotected electrical components, motors, and chords, the detailed conformity of exterior panels, the simplicity of the removable and replaceable dough scrapers, make this unit particularly simple and expedient to clean. A re-designed handle, with a comfortable sliding system, facilitates ease of dough thickness selection with a high degree of accuracy and confidence. All of these features coupled with the general ease of use make this machine unparalleled.

適合專門生產小麵包及小糕點的烘焙坊、飯店及餐廳使用。輸送帶可摺疊，不占工作空間，同時也方便清潔。電子原件、馬達、電線皆不外露，加上外嵌面板及可拆卸替換的刮刀，讓您在清潔上更加簡單方便。重新改良設計過的把手及順暢的輸送帶滑動系統，使切割出來的麵糰厚度準確一致。

性能

- 使用高級材料(不鏽鋼、鋁、合成纖維)製成，確保其符合衛生、使用壽命及耐用性的標準。輸送帶塗有聚氨酯。
- 速度可自選”節電”選項，可節省 10% 電力

自選附加功能：

- 不鏽鋼材質
- 附加切割設備
- 速度調節：兩種速度 或 使用變化器

型號 規格	LAM2 507	LAM2 510	LAM2 512	LAM2 610	LAM2 612
輸送帶尺寸 mm (長 x 寬)	495 x 850	495 x 1000	595 x 1000	595 x 1400	595 x 1000
機台展開尺寸 mm	2215 x 1165 x 970		2915 x 1165 x 970	2515 x 1165 x 1070	2915 x 1165 x 1070
機台收合尺寸 mm	970 x 1685 x 712	965 x 1723 x 1800	970 x 2016 x 940	1070 x 1826 x 810	1070 x 2016 x 2368
機台淨重 kg	170	185	190	205	210
功率 kW	0.55			0.75	
電壓 V	220 / 380 / 415 / 440 / 460 / 480				
頻率 Hz	50 – 60				
電相	3P				
輸送帶速度	標準模式：每秒 60cm 省電模式：每秒 12 – 60cm				

型號 規格	LAM2 614	LAM2 616	LAM 6510	LAM2 6514	LAM 6516
輸送帶尺寸 mm (長 x 寬)	595 x 1400	595 x 1600	645 x 1000	595 x 1200	
機台展開尺寸 mm	3315 x 1165 x 1070	3715 x 1165 x 1070	2515 x 1165 x 1108	3315 x 1165 x 1108	3715 x 1165 x 1108
機台收合尺寸 mm	1070 x 2205 x 1070	1070 x 2390 x 1200	1108 x 1826 x 810	1108 x 2205 x 1070	1108 x 2390 x 1200
機台淨重 kg	220	230	230	250	270
功率 kW	0.75		1.5		
電壓 V	220 / 380 / 415 / 440 / 460 / 480				
頻率 Hz	50 – 60				
電相	3P				
輸送帶速度	標準模式：每秒 60cm 省電模式：每秒 12 – 60cm				