

SOFT EURO / BABY

The up-to-date SOFT MACHINES are the newly-born ICETECH machines.

They are manufactured in several models and they can be divided into 1- or 3-taste counter machines, with or without a pump, as well as into 3-states machines installed on the floor with or without a pump.

ICETECH Soft machines are assisted by a modern electronic board controlling ice-cream consistency at any time by enabling the operator to monitor and to read the consistency values and the preservation temperature on the display.

ICETECH Soft machines are manufactured in order to produce really soft ice-cream having excellent consistency while enabling the operator to customize consistency just as it may wish.

The points of strength of ICETECH Soft machines are listed here below:

- Electronic control of ice- cream consistency
- Electronic control of preservation temperatures
- Basic preservation tanks of great capacity (lt.18)
- Basic level indicator in tanks
- High-overflow gear innovative formed by stirrer with counter agitator, both in stainless steel and interchangeable scrapping fins
- Tropicalised-air version for high performance levels
- High refrigerating power installed for high ice-cream production
- Ergonomic design for decoration purposes

SOFT 為 ICETECH 最新款機器。

此機器有許多型號可供選擇：小型款(BABY)可選擇 1 種口味桿或 3 種口味桿、有無幫浦；大型落地款(EURO)皆含三種口味桿，可選擇有無幫浦。

SOFT 配有現代化電子面板，任何時候都可控制冰淇淋的軟硬度，方便使用者隨時監控、了解冰淇淋的質地，同時得知溫度。

SOFT 可製作出軟硬適中的霜淇淋，同時也可讓使用者依據個人喜好設定霜淇淋的軟硬度。

SOFT 的優點為：

- 電子化控制冰淇淋質地
- 電子化控制溫度
- 上方槽容量為 18 公升
- 上方槽配有液面高度感測器
- 由攪拌器及反向攪拌器組成的高速齒輪裝置，皆由不鏽鋼製成，刮板可更換

- 耐熱氣，能製出高水平的霜淇淋
- 製冷量高
- 符合人體工學設計，方便擺飾

型號 MOD 規格 Specifications	BABY		BABY		EURO	
	1G	1P	3G	3P	3G	3P
每小時產量(一次 75g) Hourly production	430	480	450	510	520	590
上方槽容量 (Lt.) Upper tank capacity	18	18	18+18	18+18	18+18	18+18
電源 Electrical features	400V/60Hz/3Ph	400V/60Hz/3Ph	400V/60Hz/3Ph	400V/60Hz/3Ph	400V/60Hz/3Ph	400V/60Hz/3Ph
冷凝 Condensation	水/空氣 Water/Air	水/空氣 Water/Air	水/空氣 Water/Air	水/空氣 Water/Air	水/空氣 Water/Air	水/空氣 Water/Air
幫浦 Pump	無 NO	有 YES	無 NO	有 YES	無 NO	有 YES
尺寸 Sizes (mm.)	463x723x875	463x723x875	535x680x815	535x680x815	535x680x1435	535x680x1435
重量 Weight (kg.)	98	110	115	127	190	210